



深圳市力飞科技有限公司

FLY POWER INDUSTRIES LIMITED

Tel: (+86-755) 8421 4058 Fax: (+86-755) 2917 9251
 Email: info@fly-power.com Website: www.fly-power.com

Ni-MH Consumer Series

Model	Volt.	Capacity	Dimensions		Standard charge		Rapid Charge		Weight
		mAh	H(mm)	OD(mm)	mA	h	mA	min	g
FH-AAA600C	1.2	600	44.0 ± 0.5	10.0+0.3	60	16	600	72	11.5
FH-AAA700C	1.2	700	44.0 ± 0.5	10.0+0.3	70	16	700	72	11.5
FH-AAA800C	1.2	800	44.0 ± 0.5	10.0+0.3	80	16	400	140	13
FH-AAA900C	1.2	900	44.0 ± 0.5	10.0+0.3	90	16	450	140	14
FH-AA1200C	1.2	1200	49.8 ± 0.5	13.9+0.5	120	16	1200	72	22
FH-AA1400C	1.2	1400	49.8 ± 0.5	13.9+0.5	140	16	1400	72	24
FH-AA1600C	1.2	1600	49.8 ± 0.5	13.9+0.5	160	16	800	140	25.5
FH-AA1800C	1.2	1800	50.0 ± 0.5	14.1+0.5	180	16	900	140	27
FH-AA2000C	1.2	2000	50.0 ± 0.5	14.1+0.5	200	14	600	240	29
FH-AA2100C	1.2	2100	50.0 ± 0.5	14.1+0.5	210	14	630	240	30
FH-AA2300C	1.2	2300	50.0 ± 0.5	14.1+0.5	230	14	690	240	31
FH-C2500C	1.2	2500	50.5 ± 0.5	25.0+0.6	150	16	1250	140	60
FH-C4000C	1.2	4000	50.5 ± 0.5	25.0+0.6	400	16	2000	140	80
FH-C4500C	1.2	4500	50.5 ± 0.5	25.0+0.6	450	16	2250	140	90
FH-C5000C	1.2	5000	50.5 ± 0.5	25.0+0.6	500	14	1000	360	93
FH-D2500C	1.2	2500	61.5 ± 0.5	32.0+0.6	150	16	1250	140	96
FH-D6000C	1.2	6000	61.5 ± 0.5	32.0+0.6	600	16	3000	140	120
FH-D9000C	1.2	9000	61.5 ± 0.5	32.0+0.6	900	16	4500	140	170
FH-D10000C	1.2	1000	61.5 ± 0.5	32.0+0.6	1000	14	2000	360	180
FH-F7150	8.4	150	T=17.5 W=26.5 H=48.5		15	15	---	---	32
FH-F8150	9.6	150	T=17.5 W=26.5 H=48.5		15	15	---	---	36
FH-F7250	8.4	250	T=17.5 W=27.0 H=49.0		25	15	---	---	36

FH-AAA600RTU	1.2	600	44.0±0.5	10.0+0.4	60	16	600	72	11
FH-AA1200RTU	1.2	1200	48.5±0.5	13.8+0.5	120	16	1200	72	22
FH-AA1300RTU	1.2	1300	49.8±0.5	13.9+0.4	130	16	1300	72	23
FH-AA1400RTU	1.2	1400	49.8±0.5	14.0+0.5	140	16	700	140	24
FH-AA1500RTU	1.2	1500	49.8±0.5	14.0+0.5	150	16	750	140	24.5
FH-AA1600RTU	1.2	1600	49.8±0.5	14.0+0.5	160	16	800	140	25.5
FH-AA1800RTU	1.2	1800	50.0±0.5	14.0+0.5	180	16	900	140	27
FH-AA2000RTU	1.2	2000	50.0±0.5	14.0+0.5	200	15	1000	140	28.5
FH-AA2200RTU	1.2	2200	50.0±0.5	14.0+0.5	220	15	1100	140	29.5
FH-C2500RTU	1.2	2500	50.5±0.5	25.0+0.6	250	16	1250	140	60
FH-C3000RTU	1.2	3000	50.5±0.5	25.0+0.6	300	16	1500	140	66
FH-C4000RTU	1.2	4000	50.5±0.5	25.0+0.6	400	16	2000	140	80
FH-D7000RTU	1.2	7000	61.5±0.5	32.0+0.6	700	16	3500	140	133
FH-D8000RTU	1.2	8000	61.5±0.5	32.0+0.6	800	16	4000	140	155
FH-D9000RTU	1.2	9000	61.5±0.5	32.0+0.6	900	16	4500	140	170

Notes:

1. The capacities obtained at 0.1C charge and 0.2C discharge at the temperature of 25°C;
2. "C" behind the model refers to normal consumer series;
3. "RTU" behind the model refers to low self-discharge consumer series, it could obtain 70% charge reserve after 12 months at 20°C storage temperature;
4. Ambient temperature recommended for standard charging: 0°C ~ +45°C; for discharging: -20°C ~ +50°C; for storage: -20°C ~ +30°C;
5. Fly Power recommends strict control over rapid charging.