



深圳市力飞科技有限公司
FLY POWER INDUSTRIES LIMITED

Tel: (+86-755) 8421 4058 Fax: (+86-755) 2917 9251
Email: info@fly-power.com Website: www.fly-power.com

Ni-MH Standard Industrial Series

Model	volt.	capacity	Dimensions		Standard charge		Fast charge		Weight g
		mAh	H(mm)	OD(mm)	mA	h	mA	min	
FH-2/3AAA300	1.2	300	28.5 ± 0.5	10.0+0.3	30	16	300	72	7.5
FH-4/5AAA500	1.2	500	37.5 ± 0.5	10.0+0.3	50	16	500	72	10
FH-AAA600	1.2	600	42.5 ± 0.5	10.0+0.3	60	16	600	72	11.5
FH-AAA700	1.2	700	44.0 ± 0.5	10.0+0.3	70	16	700	72	11.5
FH-2/3AA600	1.2	600	28.5 ± 0.5	13.9+0.5	60	16	600	72	13
FH-2/3AA700	1.2	700	28.5 ± 0.5	13.9+0.5	70	16	700	72	14
FH-4/5AA1200	1.2	1200	42.5 ± 0.5	13.9+0.5	120	16	1200	72	21
FH-AA1200	1.2	1200	48.5 ± 0.5	13.9+0.5	120	16	1200	72	22
FH-AA1400	1.2	1400	48.5 ± 0.5	13.9+0.5	130	16	1400	72	24
FH-AA1600	1.2	1600	48.5 ± 0.5	13.9+0.5	160	16	800	140	25.5
FH-AA1800	1.2	1800	48.5 ± 0.5	14.1+0.5	180	16	900	140	27
FH-2/3A1000	1.2	1000	28.5 ± 0.5	16.6+0.5	100	16	1000	72	19.5
FH-4/5A1800	1.2	1800	42.5 ± 0.5	16.6+0.5	180	16	1800	72	31
FH-4/5A2000	1.2	2000	42.5 ± 0.5	16.6+0.5	200	16	1000	140	33
FH-A2400	1.2	2400	49.5 ± 0.5	16.6+0.5	240	16	1200	140	39
FH-4/3A3200	1.2	3200	66.5 ± 0.5	16.6+0.5	320	16	1600	140	50
FH-4/3A3500	1.2	3500	66.5 ± 0.5	16.6+0.5	350	16	1750	140	52
FH-65AF3800	1.2	3800	64.5 ± 0.5	18.0+0.5	380	16	1900	140	57
FH-67AF4100	1.2	4100	66.5 ± 0.5	18.0+0.5	400	16	2000	140	58
FH-70AF4300	1.2	4300	70.0 ± 0.5	18.0+0.5	430	16	2100	140	60
FH-4/5SC2000	1.2	2000	33.5 ± 0.5	22.0+0.6	200	16	1000	140	46
FH-SC2500	1.2	2500	42.5 ± 0.5	22.0+0.6	250	16	1250	140	55
FH-SC3000	1.2	3000	42.5 ± 0.5	22.0+0.6	300	16	1500	140	58
FH-SC3300	1.2	3300	42.5 ± 0.5	22.0+0.6	330	16	1650	140	60
FH-SC3600	1.2	3600	42.5 ± 0.5	22.0+0.6	360	16	1800	140	63
FH-C3500	1.2	3500	49.0 ± 0.5	25.0+0.6	350	16	1750	140	72
FH-C4000	1.2	4000	49.0 ± 0.5	25.0+0.6	400	16	2000	140	80
FH-1/2D4000	1.2	4000	36.5 ± 0.5	32.0+0.6	400	16	4000	140	80
FH-D6000	1.2	6000	60.0 ± 0.5	32.0+0.6	600	16	3000	140	120
FH-D8000	1.2	8000	60.0 ± 0.5	32.0+0.6	800	16	4000	140	155
FH-D9000	1.2	9000	60.0 ± 0.5	32.0+0.6	900	16	4500	140	162
FH-4/3D12000	1.2	12000	90.0 ± 0.5	32.0+0.6	1200	16	2400	360	230
FH-4/3D13000	1.2	13000	90.0 ± 0.5	32.0+0.6	1300	16	2600	360	240

Notes:

- The capacities obtained at 0.1C charge & 0.2C discharge at the temperature of 25°C;
- Ambient temperatures recommended for standard charging: 0°C ~ +45°C; for discharging: -20°C~+50°C; for storage: -20°C ~ +30°C;
- Fly Power recommends strict control over rapid charging.